

# T-3

## METAPACE T-3

Economical fully equipped top quality printer

### Technical Specifications

#### PRINT

Printing method	Direct thermal
Print speed	max. 250mm/sec.
Print width	max. 72mm
Resolution	7 points/mm (180 dpi)
Character size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24
Sensors	Paper Near End, Paper End, Cover Open

#### MEDIA

Media type	Thermal paper
Paper feed	Easy paper loading
Width	79.5mm +/- 0.5mm
Roll diameter	max. 82mm
Media strength	0.062–0.075mm

#### ELECTRONICS

Memory	64Mbit SDRAM, 16Mbit FlashROM
Interfaces	USB 2.0 and cash drawer port (RJ12) integrated, RS232, LPT, Ethernet, WLAN (optional)
Power supply	AC 100–240V, 50/60 Hz, DC 24V, 2,5A
Barcodes	All standard 1D and 2D barcodes
Emulation	ESC / POS
Reliability	150km TPH, 1,800,000 cuts, 70,000,000 lines

#### SOFTWARE

Drivers	Windows 7, 8, 10 / Linux / VCOM / OPOS / MAC
Emulation	ESC / POS
SDK	Android (starting with Version 2.2), iOS (starting with Version 5.1.1)

#### SPECIFICS

Standard	USB cable (A/B), power adapter + power cable (EU), CD (drivers, utilities), QSG, splash water cover, cable cover, cleaning pen, buzzer, test receipt roll
----------	---

#### WARRANTY

Period	5 years
--------	---------

#### HOUSING

Dimensions (WxHxD)	148 x 150 x 203mm
Colour	Black

#### CONDITIONS

Temperature	Operating: 0°C to 40°C (32°F to 104°F)
	Storage: -20°C to 60°C (-4°F to 140°F)
Humidity	Operating: 10% to 80% RH
	Storage: 10% to 90% RH

### Highlights

- + Extremely reliable direct thermal printer with a 5-year warranty
- + Lightning-quick printing of slips and receipts with up to 250mm/sec.
- + Easy connection via integrated USB port
- + Versatile options: serial, parallel, Ethernet and Wi-Fi
- + Entirely out-of-the-box: just unpack and start

